

REV.	DESCRIPTION	DATE
A	RELEASE	Nov 28,2002
B	05'0453	Apr 19,2005
C	07'0302	Mar 03,2007
D	10'0644	Jul 13,2010

MATERIALS



1. HOUSING : THERMOPLASTICS(UL 94V-0).BLACK.
2. TERMINAL : COPPER ALLOY (T=0.50mm)
GOLD PLATED ON CONTACT AREA,
UNDER NICKEL PLATED.

SPECIFICATION

1. CURRENT RATING : 1A. MAX.
2. DIELECTRIC WITHSTANDING VOLTAGE :
1000V AC R.M.S. FOR ONE MINUTE.
3. INSULATION RESISTANCE :
5000MΩ MIN. AT 500V DC.
4. CONTACT RESISTANCE : 30mΩ MAX.
5. OPERATING TEMPERATURE : -55°C TO +85°C.

ORDER INFORMATION :

1200120-X02-R
 SERIES CODE ———— ROHS
 PRESS FIT ———— FOLLOW NUMBER
 FEMALE ———— CONTACT PLATING:
 NUMBER OF POSITIONS ———— 0: GOLD FLASH
 2: 10u" GOLD PLATED

TOLERANCE .0=±0.38 .00=±0.25 .000=±.15 ANG.=±3°		DRAWER <i>Pally</i> CHECK <i>Pally</i> APP'D <i>Tomyang</i> PRODUCT SPEC. ————		 ASTRON TECHNOLOGY CORP. NAME Δ 2.0PH HEADER RECETACLE PRESS FIT 4R*30P SOLDER TAIL LENGTH 12.40mm AT LOGO	
 UNITS : mm		DRAW NO. R1200120-202			
SCALE NONE	SIZE A4	SHEET 1 OF 1	REV. D		

